

# **Status report of Latest result from the Tokyo axion helioscope experiment**

Y. Inoue,

*ICEPP, University of Tokyo*

M. Minowa, Y. Akimoto, R. Ota, T. Mizumoto,

*Department of Physics, School of Science, University of Tokyo*

A. Yamamoto

*High Energy Accelerator Research Organization (KEK)*

TAUP2007, 11 September 2007, Sendai

# Contents

- Solar axion & axion helioscope
- Tokyo axion helioscope
- Sumico Phase III

# Axion


What is the Axion?

- QCD  $\rightarrow \theta$  vacuum  $\rightarrow$  Strong CP problem (eg. neutron EDM)
- Peccei–Quinn mechanism:  
global chiral U(1) + SSB  
 $\rightarrow \underline{\text{NG boson}} + \frac{(1/32\pi^2 f_a)aF_a\tilde{F}_a}{\downarrow \qquad \qquad \downarrow}$   
axion      resolves Strong CP

Searches/Limits:

- Experiments: Accelerator, Reactor, Nuclear transition, Telescope,  
Solar axion, Laser, Microwave cavity, ...
- Astrophysics: Solar axion, Red giants, SN1987A
- Cosmology:  $\Omega_a < 1$


# Exclusion plot ( $g_{a\gamma}$ vs $m_a$ )




[L.J. Rosenberg, K.A. van Bibber, Phys. Rep. 325(2000)1]

## Solar axion

The sun can be a powerful source of axions. In the solar core, axions can be produced from photons through the Primakoff process.




K.van Bibber *et al.*, PRD39(1989)2089



# Axion telescope

[P. Sikivie, Phys. Rev. Lett. 51(1983)1415]

The solar axions can be reconverted into x-rays using a strong magnetic field in a laboratory.



## Conversion rate

Conversion rate:

$$P_{a \rightarrow \gamma} = \frac{g_{a\gamma}^2}{2} \left| \int_0^L B e^{iqz} dz \right|^2 = \frac{g_{a\gamma}^2 B^2}{q^2} \sin^2 \frac{qL}{2},$$

$$q = m_a^2/2E. \quad (\text{momentum transfer})$$


The coherence is lost for  $m_a \gtrsim \sqrt{\pi E/L} \dots$


But coherence can be restored by filling the conversion region with buffer gas. In buffer gas, the momentum transfer becomes

$$q = |m_\gamma^2 - m_a^2|/2E,$$


$$m_\gamma = \sqrt{\frac{4\pi\alpha N_e}{m_e}}. \quad (\text{effective photon mass})$$

# Sumico V detector






# Past measurements & results



- Phase I — vacuum  
 $m_a < 0.03$  eV  
1997 December  
[S. Moriyama *et al.*, Phys. Lett. B 434(1998)147]
- Phase II — low density He  
 $m_a < 0.27$  eV  
( $p < 2$  kPa,  $T = 5.2$ – $5.7$  K)  
2000 July–September  
[Y. Inoue, *et al.*, Phys. Lett. B 536(2002)18]

# CAST @ CERN

[Zioutas *et al.*, PRL94(2005)121301]




[Irastorza *et al.*,  
Rencontres de Moriond EW2007]  
<http://moriond.in2p3.fr/EW/2007/>

- $B = 9 \text{ T}$ ,  $L = 9.26 \text{ m}$   
(LHC test magnet)
- Vertical  $\pm 8^\circ$ , horizontal  $\pm 40^\circ$
- TPC, Micromegas,  
CCD+mirror



# What's next? — Sumico Phase III




- Phase I — vacuum  
 $m_a < 0.03 \text{ eV}$   
1997 December  
[S. Moriyama *et al.*, Phys. Lett. B 434(1998)147]
- Phase II — low density He  
 $m_a < 0.27 \text{ eV}$   
( $p < 2 \text{ kPa}, T = 5.2\text{--}5.7 \text{ K}$ )  
2000 July–September  
[Y. Inoue, *et al.*, Phys. Lett. B 536(2002)18]
- Phase III — high density He  
 $m_a \lesssim 2.2\text{--}2.6 \text{ eV}$   
( $p \lesssim 1\text{--}2 \text{ atm}, T = 5\text{--}6 \text{ K}$ )

## How to resist magnet quench?

When the superconducting magnet quenches, its temperature rises up to 50–60 K within a few seconds.

- No good commercial cryogenic relief valve
- Know thy enemy.

Measured the pressure change after a forced quench.



→ Not as fast as the magnet: use  $\phi 1/4"$  tube


## And a rupture disk



- Hydrodyne
- Cryogenic precision burst disc
- $36 \text{ psi} \pm 5\% @ 5 \text{ K}$
- Exhaust through a normally evacuated  $3/8"$  line.


## Resonance width at high $m_a$

$$P_{a \rightarrow \gamma} = \frac{g_{a\gamma}^2 B^2}{q^2} \sin^2 \frac{qL}{2}; \quad q = |m_\gamma^2 - m_a^2|/2E$$




- $\delta N_{\text{He}}/N_{\text{He}} < 0.1\%$   
stabilize  $T + \text{control } p$ .  
$$N_{\text{He}} = \frac{p}{RT}$$
- Many many data points  
to scan  
→ computer control

# Temperature stabilization




# Gas container




- Compact design
- Welded 4 × st. steel 304  
 $21.9 \times 17.9 \times 2300 \text{ mm}^3$   
square pipes
- Pure Al (99.999%)  
0.1-mm thick,  
× 2 layers
- Measured thermal conductivity  
 $\gtrsim 10^{-2} \text{ W/K}$   
@ 5 K, 4 T

# Gas controlling system



# Test result of $p, T$ control

$p \sim 15 \text{ kPa}, T = 5.75 \text{ K}$



Excellent!

## Other progress / status

- PIN diode dead layer measurement
- Moved to a new site ... again
- Reconstruction — almost finished, left final precision alignment
- True north direction by gyrocompass
- Repaired and refined mechanics of altazimuth stage
- Cable handling robot — work in progress, half done
- Repairing broken cables — work in progress

## Summary

- Sumico Phase III will explore  $m_a \lesssim 2.2\text{--}2.6\,\text{eV}$
- Most technical difficulties have been overcome.
- Now the magnet has been cooled.  
 $T_{\text{mag}} = 6\,\text{K}$  as of 10 September
- Measurement will start soon.